



## FLX-AIR/10

Air Discharge hose - 10 BAR W.P.

### Application

Discharge hose for compressed air used with pneumatic tools.

### Tube

Black smooth, synthetic rubber compound resistant to oil mist.

### Reinforcement

High strength synthetic cord.

### Cover

Wrapped impression, abrasion and weather resistant SBR/EPDM rubber compound.

### Temp. Range

-30°C to +80°C; -22°F to 176°F

ID		OD	WP		BP		BR	W	L
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/2"	12.7	22	10	150	40	600	127	362	61
5/8"	16	25	10	150	40	600	160	446	61
3/4"	19	29	10	150	40	600	190	506	61
1"	25.4	36	10	150	40	600	254	748	61
1 1/4"	32	44	10	150	40	600	320	1058	61
1 1/2"	38	51	10	150	40	600	380	1349	61
1 3/4"	44.5	57	10	150	40	600	445	1434	61
2"	51	63	10	150	40	600	510	1628	61
2 1/2"	63.5	78	10	150	40	600	635	2381	61
3"	76.2	92	10	150	40	600	762	3093	61
4"	101.6	117	10	150	40	600	1016	3851	61

Conforms to TS EN ISO 2398:2017 Type 1 Class A