



## FLX-AIR/20

Medium Duty Air Discharge Hose - 20 BAR W.P.

### Application

Discharge hose for compressed air used with pneumatic tools.

### Tube

Black smooth, synthetic rubber compound resistant to oil mist.

### Reinforcement

High strength synthetic cord.

### Cover

Wrapped impression, abrasion and weather resistant SBR/EPDM rubber compound.

### Temp. Range

-30°C to +80°C; -22°F to 176°F

ID		OD		WP		BP		BR		W		L	
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt				
1/2"	12.7	23	20	300	60	900	127	371	61				
5/8"	16	26	20	300	60	900	160	428	61				
3/4"	19	30	20	300	60	900	190	579	61				
1"	25.4	37	20	300	60	900	254	798	61				
1 1/4"	32	44	20	300	60	900	320	1002	61				
1 1/2"	38	52	20	300	60	900	380	1410	61				
1 3/4"	44.5	61	20	300	60	900	445	1630	61				
2"	51	67	20	300	60	900	510	2105	61				
2 1/2"	63.5	80	20	300	60	900	635	2550	61				
3"	76.2	94	20	300	60	900	762	3342	61				
4"	101.6	120	20	300	60	900	1016	3912	61				

Conforms to TS EN ISO 2398:2017 Type 2 Class A 