



FLX-AIR/25

Heavy Duty Air Discharge Hose - 25 BAR W.P.

Application

Discharge hose for compressed air used with pneumatic tools.

Tube

Black smooth, synthetic rubber compound resistant to oil mist.

Reinforcement

High strength synthetic cord.

Cover

Wrapped impression, abrasion and weather resistant SBR/EPDM rubber compound.

Temp. Range

-30°C to +80°C; -22°F to 176°F

ID		OD		WP		BP		BR		W		L	
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt				
1/2"	12.7	24	25	363	75	1088	127	427	61				
5/8"	16	28	25	363	75	1088	160	538	61				
3/4"	19	32	25	363	75	1088	190	697	61				
1"	25.4	39	25	363	75	1088	254	931	61				
1 1/4"	32	48	25	363	75	1088	320	1429	61				
1 1/2"	38	54	25	363	75	1088	380	1592	61				
1 3/4"	44.5	61	25	363	75	1088	445	1739	61				
2"	51	69	25	363	75	1088	510	2310	61				
2 1/2"	63.5	83	25	363	75	1088	635	3210	61				
3"	76.2	96	25	363	75	1088	762	3782	61				
4"	101.6	124	25	363	75	1088	1016	5683	61				