



FLX-CEMENT D/10

DRY CEMENT DISCHARGE HOSE -10 Bar W.P.

Application	Transfer of cement, gravel, sand and general abrasive dry materials.
Tube	Black, smooth, anti-static NR/SBR rubber compound.
Reinforcement	High strength synthetic plies, anti-static copper wire.
Cover	Wrapped impression, abrasion and weather resistant, anti-static, pin-pricked, NR/SBR rubber compound.
Temp. Range	-40°C to +85°C ; -40°F to 185°F

ID		OD	WP		BP		W	L
inch	mm	mm	BAR	PSI	BAR	PSI	gr/mt	mt
1"	25.4	37	10	150	30	450	635	61
1 1/4"	32	44	10	150	30	450	824	61
1 1/2"	38	50	10	150	30	450	975	61
1 3/4"	44.5	58	10	150	30	450	1291	61
2"	50.8	64.5	10	150	30	450	1485	61
2 1/2"	63.5	77	10	150	30	450	1754	61
3"	76.2	90	10	150	30	450	2150	61
3 1/2"	90	104	10	150	30	450	2610	61
4"	101.6	118	10	150	30	450	3286	61
5"	127	146	10	150	30	450	4915	61
6"	152.4	172	10	150	30	450	6227	61
8"	203.2	225	10	150	30	450	8910	20
10"	254	276	10	150	30	450	12153	20

Abrasion loss value of the tube $\leq 50 \text{ mm}^3$ (according to DIN ISO 4649:2006)