



FLX-CRETE 85

TEXTILE CONCRETE HOSE - 85 Bar W.P.

Application	High pressure concrete placement hose used in construction.
Tube	Black, smooth, anti-static, NR/SBR rubber compound.
Reinforcement	High strength synthetic plies, anti-static copper wire.
Cover	Wrapped impression, abrasion and weather resistant, anti-static, pin-pricked, NR/SBR rubber compound.
Temp. Range	-40°C to +85°C ; -40°F to 185°F



ID



OD



WP



BP



W



L

ID		OD		WP		BP		W	L
inch	mm	inch	mm	BAR	PSI	BAR	PSI	gr/mt	mt
1 1/4"	32	1.92	48.8	85	1233	170	2466	1217	61
1 1/2"	38	2.31	58.7	85	1233	170	2466	1833	61
2"	50.8	2.83	72	85	1233	170	2466	2397	61
2 1/2"	63.5	3.39	86.2	85	1233	170	2466	3009	61
3"	76.2	3.93	99.6	85	1233	170	2466	3647	61
3 1/2"	90	4.49	114	85	1233	170	2466	4119	61
4"	101.6	4.95	125.8	85	1233	170	2466	4732	61
5"	127	6.06	154	85	1233	170	2466	6370	61

Abrasion loss value of the tube $\leq 50 \text{ mm}^3$ (according to DIN ISO 4649:2006)