



## FLX-HOT WATER CHanneLED

Hot Water Suction and Delivery -5 Bar W.P.

### Application

Suction and delivery of hot water and coolant fluids, mild chemicals used in cooling and heating systems. Channeled construction provides superior flexibility.

### Tube

Black, smooth, EPDM rubber compound.

### Reinforcement

High strength synthetic plies and steel wire spirals.

### Cover

Wrapped impression, channeled, abrasion and weather resistant EPDM rubber compound.

### Temp. Range

-40°C to +125°C ; -40°F to 257°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
19/32"	15	23	5	75	15	225	0.80	55	419	61
5/8"	16	24	5	75	15	225	0.80	60	452	61
23/32"	18	26	5	75	15	225	0.80	65	478	61
3/4"	19	27	5	75	15	225	0.80	71	502	61
25/32"	20	28	5	75	15	225	0.80	72	524	61
7/8"	22	30	5	75	15	225	0.80	75	551	61
1"	25.4	33	5	75	15	225	0.80	85	582	61
1 3/32"	28	36	5	75	15	225	0.80	97	639	61
1 3/16"	30	38	5	75	15	225	0.80	101	691	61
1 1/4"	32	40	5	75	15	225	0.80	106	735	61
1 3/8"	35	43	5	75	15	225	0.80	117	836	61
1 1/2"	38	47	5	75	15	225	0.80	132	934	61
1 9/16"	40	49	5	75	15	225	0.80	135	1013	61
1 25/32"	45	54	5	75	15	225	0.80	141	1194	61
2"	51	61	5	75	15	225	0.80	160	1315	61
2 3/8"	60	70	5	75	15	225	0.80	180	1652	61
2 1/2"	63.5	73	5	75	15	225	0.80	200	1710	61
3"	76.2	90	5	75	15	225	0.80	457	2552	61
4"	101.6	115	5	75	15	225	0.80	610	3628	61