



FLX-OIL SD/10 CHanneLED

Oil Suction and Delivery Hose 10 Bar W.P.

Application

Extremely flexible oil suction and delivery hose used in transfer of mineral oils, diesel fuel and gasoline with aromatic content up to 50%.

Tube

Black, smooth, NBR rubber compound.

Reinforcement

High strength synthetic plies and steel wire spirals, conductive copper wire.

Cover

Square corrugated, wrapped impression, abrasion and weather resistant synthetic rubber compound.

Temp. Range

-40°C to +100°C ; -40°F to 212°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
3/4"	19	28	10	150	30	450	0.9	60	590	61
1"	25.4	34	10	150	30	450	0.9	80	720	61
1 1/4"	32	42	10	150	30	450	0.9	105	985	61
1 1/2"	38	48	10	150	30	450	0.9	120	1150	61
1 9/16"	40	50	10	150	30	450	0.9	135	1210	61
1 3/4"	44.5	55	10	150	30	450	0.9	150	1390	61
2"	50.8	63	10	150	30	450	0.9	165	1610	61
2 3/8"	60	72	10	150	30	450	0.9	180	1800	61
2 1/2"	63.5	74	10	150	30	450	0.9	195	1910	61
3"	76.2	90	10	150	30	450	0.9	230	2847	61
4"	101.6	116	10	150	30	450	0.9	310	4192	61