



FLX-OIL SD/10

Oil Suction and Delivery Hose -10 Bar W.P.

Application

Transfer of fuels, oils and other petroleum derivatives with up to 50% aromatic content.

Tube

Black, smooth, NBR rubber compound.

Reinforcement

High strength synthetic plies and steel wire spirals. Copper wire added for grounding.

Cover

Wrapped impression, abrasion and weather resistant special synthetic rubber compound.

Temp. Range

-30°C to +80°C ; -22°F to 176°F

ID		OD		WP		BP		VACUUM		BR		W		L	
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt					
3/4"	19	29	10	150	30	450	0.9	120	610	61					
1"	25.4	36	10	150	30	450	0.9	150	815	61					
1 1/4"	32	43	10	150	30	450	0.9	190	1120	61					
1 1/2"	38	49	10	150	30	450	0.9	240	1217	61					
1 3/4"	44.5	56	10	150	30	450	0.9	270	1412	61					
2"	50.8	63	10	150	30	450	0.9	300	1788	61					
2 1/2"	63.5	76	10	150	30	450	0.9	380	2198	61					
3"	76.2	89	10	150	30	450	0.9	460	2954	61					
3 1/2"	90	105	10	150	30	450	0.9	540	3612	61					
4"	101.6	117	10	150	30	450	0.9	600	4320	61					
5"	127	145	10	150	30	450	0.9	760	6188	61					
6"	152.4	170	10	150	30	450	0.9	900	7723	61					