



FLX-OIL SD/20 CORRUGATED

Corrugated Oil Suction and Delivery
Hose -20 Bar W.P.

Application

High pressure suction and discharge of fuels, oils and other petroleum derivatives with up to 50% aromatic content. Corrugated construction provides flexibility and makes it easier to drag the hose by reducing friction.

Tube

Black, smooth, NBR rubber compound.

Reinforcement

High strength synthetic plies and steel wire spirals. Copper wire added for grounding.

Cover

Corrugated, wrapped impression, abrasion and weather resistant special synthetic rubber compound.

Temp. Range

-30°C to +80°C ; -22°F to 176°F

ID		OD		WP		BP		VACUUM	BR	W	L
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt	
1"	25.4	38	20	300	60	900	0.9	85	978	61	
1 1/4"	32	44	20	300	60	900	0.9	100	1035	61	
1 1/2"	38	51	20	300	60	900	0.9	125	1354	61	
2"	50.8	65	20	300	60	900	0.9	231	2083	61	
2 1/2"	63.5	79	20	300	60	900	0.9	250	2739	61	
3"	76.2	92	20	300	60	900	0.9	335	3389	61	
4"	101.6	118	20	300	60	900	0.9	439	4683	61	
5"	127	148	20	300	60	900	0.9	578	7187	61	
6"	152.4	175	20	300	60	900	0.9	700	9609	61	
8"	203.2	231	20	300	60	900	0.8	1130	15165	20	