



FLX-PLASTER 40

PLASTER HOSE - 40 Bar W.P.

Application	High pressure spray of plaster, grout, gypsum and mixed concrete in construction and shipyards.
Tube	Black, smooth, static-dissipating NR/SBR rubber compound.
Reinforcement	High strength synthetic plies, anti-static copper wire.
Cover	Wrapped impression, abrasion and weather resistant, static-dissipating, pin-pricked, NR/SBR rubber compound.
Temp. Range	-40°C to +85°C ; -40°F to 185°F

ID		OD	WP		BP		BR	W	L
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
3/4"	19	31	40	580	120	1740	120	612	61
1"	25.4	37	40	580	120	1740	148	738	61
1"	25.4	38	40	580	120	1740	150	795	61
1 3/16"	30	44	40	580	120	1740	176	1057	61
1 1/4"	32	46	40	580	120	1740	184	1114	61
1 3/8"	35	49	40	580	120	1740	196	1200	61
1 3/8"	35	51	40	580	120	1740	202	1398	61
1 1/2"	38	54	40	580	120	1740	210	1502	61
1 9/16"	40	56	40	580	120	1740	224	1567	61
1 3/4"	44.5	61	40	580	120	1740	244	1776	61
2"	50.8	68	40	580	120	1740	290	2064	61
2 3/8"	60	80	40	580	120	1740	350	2857	61
2 1/2"	63.5	83.5	40	580	120	1740	375	3000	61
2 5/8"	65	85	40	580	120	1740	390	3061	61
2 3/4"	70	90	40	580	120	1740	405	3265	61
3"	76.2	96.2	40	580	120	1740	432	3518	61
4"	101.6	127	40	580	120	1740	572	5842	61

Abrasion loss value of the tube ≤ 50 mm³ (according to DIN ISO 4649:2006)