



FLX-SAND 2PLY

**2-PLY SANDBLAST HOSE 10 Bar W.P.
1/4" tube thickness.**

Application

Used in conveying sand, shot, glass beads and other abrasive materials at high velocity for cleaning metal, concrete surfaces at shipyards and general construction.

Tube

Black, smooth, static-dissipating NR/SBR rubber compound. 1/4" tube thickness.

Reinforcement

High strength 2 synthetic plies.

Cover

Wrapped impression, abrasion and weather resistant, pin-pricked, static-dissipating, NR/SBR rubber compound.

Temp. Range

-40°C to +85°C ; -40°F to 185°F



ID



OD



WP



BP



W



L

inch	mm	mm	inch	BAR	PSI	BAR	PSI	gr/mt	mt
1/2"	12.7	25.4	1.00	10	150	30	450	460	61
1/2"	12.7	26.9	1.06	10	150	30	450	544	61
1/2"	12.7	28.5	1.13	10	150	30	450	620	61
1/2"	12.7	30.2	1.19	10	150	30	450	710	61
3/4"	19	38.1	1.50	10	150	30	450	987	61
1"	25.4	47	1.85	10	150	30	450	1416	61
1 1/4"	32	47.6	1.88	10	150	30	450	1143	61
1 1/4"	32	54.7	2.16	10	150	30	450	1819	61
1 1/2"	38	60.3	2.38	10	150	30	450	2003	61
2"	50.8	73	2.88	10	150	30	450	2549	61

Abrasion loss value of the tube $\leq 50 \text{ mm}^3$ (according to DIN ISO 4649:2006)