



FLX-WTR D/10

Water Delivery - 10 BAR W.P.

Application

Delivery hose for water, compressed air, non-corrosive fluids, used in construction, mining and general dewatering applications.

Tube

Black smooth, synthetic rubber compound.

Reinforcement

High strength synthetic cord.

Cover

Wrapped impression, abrasion and weather resistant SBR/EPDM rubber compound.

Temp. Range

-30°C to +80°C ; -22°F to 176°F



ID



OD



WP



BP



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/2"	12.7	21	10	150	30	450	127	320	61
5/8"	16	24	10	150	30	450	160	380	61
3/4"	19	27	10	150	30	450	190	450	61
1"	25.4	33	10	150	30	450	254	528	61
1 1/4"	32	42	10	150	30	450	320	810	61
1 1/2"	38	47	10	150	30	450	380	920	61
1 3/4"	44.5	54	10	150	30	450	445	1195	61
2"	50.8	60	10	150	30	450	510	1390	61
2 1/2"	63.5	74	10	150	30	450	635	1810	61
2 3/4"	70	82	10	150	30	450	700	2180	61
3"	76.2	87	10	150	30	450	762	2260	61
4"	101.6	115	10	150	30	450	1016	3345	61
5"	127	140	10	150	30	450	1270	3950	61
6"	152.4	165	10	150	30	450	1524	4834	61
8"	203.2	222	10	150	30	450	2032	9319	20-40
10"	254	272	10	150	30	450	2540	12100	20