



FLX-CEMENT SD/10 CORRUGATED

DRY CEMENT SUCTION & DISCHARGE
HOSE -10 Bar W.P. CORRUGATED

Application

Transfer of cement, gravel, sand and general abrasive dry materials.

Tube

Black, smooth, anti-static NR/SBR rubber compound.

Reinforcement

High strength synthetic plies, steel wire helix, anti-static copper wire.

Cover

Corrugated, wrapped impression, abrasion and weather resistant, anti-static, pin-pricked NR/SBR rubber compound.

Temp. Range

-40°C to +85°C ; -40°F to 185°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
2"	50.8	67	10	150	30	450	0.9	190	2010	61
2 1/2"	63.5	78	10	150	30	450	0.9	240	2425	61
3"	76.2	92	10	150	30	450	0.9	290	3241	61
3 1/2"	90	107	10	150	30	450	0.9	360	3905	61
4"	101.6	120	10	150	30	450	0.9	450	4690	61
5"	127	150	10	150	30	450	0.9	550	6810	61
6"	152.4	175	10	150	30	450	0.9	650	9150	61
8"	203.2	229	10	150	30	450	0.9	1100	14180	20
10"	254	281	10	150	30	450	0.9	1400	17830	20