



## FLX-CHEM SD/10 CORRUGATED

Chemical Suction and Delivery Hose  
EPDM -10 Bar W.P. Corrugated

### Application

Transfer of chemicals, urban and industrial wastewater discharge of mixed content.  
For suitable fluids please check chemical resistance chart at the end of the catalog.

### Tube

Black, smooth, antistatic EPDM rubber compound.

### Reinforcement

High strength synthetic plies, helix wire, conductive copper wire.

### Cover

Wrapped impression, abrasion, weather and heat resistant corrugated EPDM rubber compound.

### Temp. Range

-40°C to +100°C ; -40°F to 212°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
3/4"	19	31	10	150	30	450	0.9	100	700	61
1"	25.4	37	10	150	30	450	0.9	122	850	61
1 1/4"	32	44	10	150	30	450	0.9	145	1150	61
1 1/2"	38	51	10	150	30	450	0.9	168	1400	61
2"	50.8	67	10	150	30	450	0.9	221	1890	61
2 1/2"	63.5	80	10	150	30	450	0.9	264	2600	61
3"	76.2	92	10	150	30	450	0.9	303	3460	61
4"	101.6	118	10	150	30	450	0.9	389	4450	61