



FLX-OIL SD/10 CORRUGATED

Corrugated Oil Suction and Delivery
Hose -10 Bar W.P.

Application

Transfer of fuels, oils and other petroleum derivatives with up to 50% aromatic content. Corrugated construction provides flexibility and makes it easier to drag the hose by reducing friction.

Tube

Black, smooth, NBR rubber compound.

Reinforcement

High strength synthetic plies and steel wire spirals. Copper wire added for grounding.

Cover

Corrugated, wrapped impression, abrasion and weather resistant special synthetic rubber compound.

Temp. Range

-30°C to +80°C ; -22°F to 176°F

ID		OD		WP		BP		VACUUM	BR	W	L
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt	
3/4"	19	29	10	150	30	450	0.9	71	476	61	
1"	25.4	37	10	150	30	450	0.9	87	623	61	
1 1/4"	32	44	10	150	30	450	0.9	116	865	61	
1 1/2"	38	50	10	150	30	450	0.9	134	1010	61	
1 3/4"	44.5	57	10	150	30	450	0.9	157	1318	61	
2"	50.9	64	10	150	30	450	0.9	186	1522	61	
2 1/2"	63.5	77	10	150	30	450	0.9	230	2130	61	
3"	76.2	90	10	150	30	450	0.9	298	2615	61	
4"	101.6	116	10	150	30	450	0.9	390	3851	61	
5"	127	145	10	150	30	450	0.9	510	6260	61	
6"	152.4	172	10	150	30	450	0.9	620	8741	61	
8"	203.2	225	10	150	30	450	0.8	814	12306	20	