



## FLX-SAND 4PLY

**4-PLY SANDBLAST HOSE 10 Bar W.P.  
1/4" tube thickness.**

### Application

Used in conveying sand, shot, glass beads and other abrasive materials at high velocity for cleaning metal, concrete surfaces at shipyards and general construction.

### Tube

Black, smooth, static-dissipating, NR/SBR rubber compound. 1/4" tube thickness.

### Reinforcement

High strength 4 synthetic plies.

### Cover

Wrapped impression, abrasion and weather resistant, static-dissipating, pin-pricked, NR/SBR rubber compound.

### Temp. Range

-40°C to +85°C ; -40°F to 185°F



ID



OD



WP



BP



W



L

inch	mm	mm	inch	BAR	PSI	BAR	PSI	gr/mt	mt
1/2"	13	28.5	1.13	10	150	30	450	641	61
3/4"	19	38.1	1.50	10	150	30	450	1048	61
1"	25.4	47.6	1.88	10	150	30	450	1556	61
1 1/4"	32	54.7	2.16	10	150	30	450	1898	61
1 1/2"	38	60.3	2.38	10	150	30	450	2027	61
2"	50.8	73.3	2.88	10	150	30	450	2528	61

Abrasion loss value of the tube  $\leq 50 \text{ mm}^3$  (according to DIN ISO 4649:2006)