



FLX-STEAM 170C

Low pressure steam hose 170°C

Application

Low pressure saturated steam discharge hose, used in steam cleaning applications.

Tube

Black smooth, EPM rubber compound.

Reinforcement

High strength synthetic cords.

Cover

Wrapped impression, heat, abrasion and weather resistant, pin-pricked EPDM rubber compound.

Temp. Range

-40°C to +170°C ; -40°F to 338°F



ID



OD



WP



BP



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/2"	12.7	24	7	102	70	1015	81	363	61
5/8"	16	28	7	102	70	1015	101	462	61
3/4"	19	31	7	102	70	1015	136	525	61
1"	25.4	37	7	102	70	1015	171	607	61
1 1/4"	32	46	7	102	70	1015	241	944	61
1 1/2"	38	53	7	102	70	1015	301	1167	61
1 3/4"	44.5	60	7	102	70	1015	336	1405	61
2"	50.8	67.5	7	102	70	1015	376	1750	61
2 1/2"	63.5	81	7	102	70	1015	501	2234	61
3"	76.2	98	7	102	70	1015	611	3316	61
4"	101.6	124	7	102	70	1015	816	4450	61