



FLX-WTR D/7

Water Delivery - 7 BAR W.P.

Application

Delivery hose for water, general watering and gardening applications.

Tube

Black smooth, synthetic rubber compound.

Reinforcement

High strength synthetic cord.

Cover

Wrapped impression, abrasion and weather resistant synthetic rubber compound.

Temp. Range

-30°C to +80°C ; -22°F to 176°F



ID



OD



WP



BP



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	gr/mt	mt
1/2"	12.7	21	7	102	21	305	310	61
5/8"	16	24	7	102	21	305	368	61
3/4"	19	27	7	102	21	305	428	61
1"	25.4	33	7	102	21	305	520	61
1 1/4"	32	40	7	102	21	305	640	61
1 1/2"	38	46	7	102	21	305	752	61
1 3/4"	44.5	53	7	102	21	305	942	61
2"	50.8	60	7	102	21	305	1200	61
2 1/2"	63.5	73	7	102	21	305	1510	61
2 3/4"	70	80	7	102	21	305	1796	61
3"	76.2	86	7	102	21	305	1920	61
4"	101.6	112	7	102	21	305	2610	61
5"	127	139	7	102	21	305	3618	61
6"	152.4	165	7	102	21	305	4712	61
8"	203.2	218	7	102	21	305	7498	20
10"	254	270	7	102	21	305	10122	20

Conforms to TS EN ISO 1403:2019 Type 1