



## FLX-YELLOW AIR 400

**Heavy Duty Air  
Discharge Hose - 400 PSI W.P.**

### Application

Heavy duty Air and Water applications in mines, quarries, construction sites.

### Tube

Black smooth, synthetic rubber compound resistant to oil mist.

### Reinforcement

High strength 2-ply synthetic cords

### Cover

Wrapped impression, abrasion and weather resistant, pin-pricked synthetic rubber compound.

### Temp. Range

-35°C to +93°C ; -30°F to 200°F



ID



OD



WP



BP



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/2"	12.7	23	27.6	400	82.8	1200	127	418	61
5/8"	16	27	27.6	400	82.8	1200	160	512	61
3/4"	19	31	27.6	400	82.8	1200	190	621	61
1"	25.4	38	27.6	400	82.8	1200	254	798	61
1 1/4"	32	47	27.6	400	82.8	1200	320	1229	61
1 1/2"	38	52	27.6	400	82.8	1200	380	1410	61
1 3/4"	44.5	61	27.6	400	82.8	1200	445	1739	61
2"	51	67	27.6	400	82.8	1200	510	2217	61
2 1/2"	63.5	82	27.6	400	82.8	1200	635	2910	61
3"	76.2	94	27.6	400	82.8	1200	762	3411	61
4"	101.6	120	27.6	400	82.8	1200	1016	4355	61