



FLX-DRY BULK SD/5 CORRUGATED

1/4" GUM TUBE- 5 Bar W.P.
CORRUGATED

Application

Suction, delivery or gravity flow of gravel, sand and general abrasive dry materials.

Tube

Highly abrasion resistant 1/4" thick gum tube.

Reinforcement

High tensile textile plies, steel wire helix, anti-static copper wire.

Cover

Black, corrugated, wrapped impression, abrasion, ozone and weather resistant, synthetic rubber.

Temp. Range

-40°C to +70°C ; -40°F to 158°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
1 1/4"	32	44	5	75	15	225	0.9	70	935	61
1 1/2"	38	51	5	75	15	225	0.9	85	1246	61
2"	50.8	65	5	75	15	225	0.9	130	1710	61
2 1/2"	63.5	78	5	75	15	225	0.9	175	2344	61
3"	76.2	91	5	75	15	225	0.9	195	2975	61
3 1/2"	90	106	5	75	15	225	0.9	230	3790	61
4"	101.6	119	5	75	15	225	0.9	275	4586	61
5"	127	147	5	75	15	225	0.9	520	6610	61
6"	152.4	173	5	75	15	225	0.9	590	8750	61
8"	203.2	227	5	75	15	225	0.8	980	13980	20
10"	254	279	5	75	15	225	0.8	1200	16930	20