



FLX-LPG EN1762 TYPE D

LPG discharge hose -25 Bar W.P.

Application

Pump hose for vehicle refueling and bulk loading from tankers of liquified petroleum according to EN 1762. Hose is suitable for transfer of natural gas as well.

Tube

Black, smooth, electrically conductive NBR compound.

Reinforcement

High strength synthetic textile plies, 2 crossing conductive copper wires.

Cover

Wrapped impression, electrically conductive, fireproof CR rubber compound, resistant to abrasion, weather, ozone, oil and heat.

Temp. Range

-30°C to +70°C; -22°F to 158°F



ID



OD



WP



BP



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/2"	12.7	23	25	363	100	1450	100	390	61
5/8"	16	26	25	363	100	1450	120	470	61
3/4"	19	31	25	363	100	1450	160	650	61
1"	25.4	38	25	363	100	1450	200	840	61
1 1/4"	32	45	25	363	100	1450	250	1050	61
1 1/2"	38	52	25	363	100	1450	320	1300	61
2"	50.8	67	25	363	100	1450	400	1900	61
2 1/2"	63.5	81	25	363	100	1450	550	2500	61
3"	76.2	94	25	363	100	1450	650	3040	61
4"	101,6	120	25	363	100	1450	800	3860	61