



FLX-SEWER VAC SD/10 CORRUGATED

SEWER TRUCK VACUUM HOSE-
10 Bar W.P.

Application

Heavy duty suction hose used in sewer and waste suction trucks, industrial vacuum of drill cuttings, tank bottoms, heavy crude sludge and sand slurries.

Tube

Highly abrasion resistant red NR tube.

Reinforcement

High tensile textile plies, steel wire helix, anti-static copper wire.

Cover

Black, corrugated, wrapped impression, abrasion, ozone and weather resistant, conductive NR/SBR compound.

Temp. Range

-40°C to +80°C ; -40°F to 176°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
2"	50.8	69	10	150	30	450	0.9	160	2157	61
3"	76.2	96	10	150	30	450	0.9	230	3587	61
4"	101.6	122	10	150	30	450	0.9	310	5085	61
5"	127	149	10	150	30	450	0.9	390	6673	61
6"	152.4	174	10	150	30	450	0.9	610	8689	61
8"	203.2	227	10	150	30	450	0.8	815	13744	20
10"	254	283	10	150	30	450	0.8	1020	20782	20