



FLX-CHEM SD/10 EPDM Chemical Suction and Delivery Hose EPDM -10 Bar W.P.

Application

Transfer of chemicals, urban and industrial wastewater discharge of mixed content. For suitable fluids please check chemical resistance chart at the end of the catalog.

Tube

Black, smooth, EPDM rubber compound.

Reinforcement

High strength synthetic plies, helix wire, conductive copper wire.

Cover

Wrapped impression, abrasion, weather and heat resistant EPDM rubber compound.

Temp. Range

-40°C to +100°C ; -40°F to 212°F



ID



OD



WP



BP



VACUUM



BR



W



L

inch		mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt
3/4"	19	30	10	150	40	600	0.9	120	620	61	
1"	25.4	36	10	150	40	600	0.9	140	745	61	
1 1/4"	32	44	10	150	40	600	0.9	176	1100	61	
1 1/2"	38	51	10	150	40	600	0.9	204	1394	61	
2"	50.8	66	10	150	40	600	0.9	264	2230	61	
2 1/2"	63.5	79	10	150	40	600	0.9	316	2816	61	
3"	76.2	92	10	150	40	600	0.9	368	3360	61	
4"	101.6	118	10	150	40	600	0.9	472	4120	61	