



FLX-OIL SD/10

Oil Suction and Delivery Hose -10 Bar W.P.

Application

Transfer of fuels, oils and other petroleum derivatives up to 50% aromatic content.

Tube

Black, smooth, NBR rubber compound.

Reinforcement

High strength synthetic plies, steel helix wire, conductive copper wire.

Cover

Wrapped impression, abrasion and weather resistant special synthetic rubber compound.

Temp. Range

-30°C to +80°C ; -22°F to 176°F

ID		OD		WP		BP		VACUUM	BR	W	L
inch	mm	mm	BAR	PSI	BAR	PSI	BAR	mm	gr/mt	mt	
3/4"	19	29	10	150	30	450	0.9	120	590	61	
1"	25.4	35	10	150	30	450	0.9	150	710	61	
1 1/4"	32	42	10	150	30	450	0.9	190	915	61	
1 1/2"	38	48	10	150	30	450	0.9	240	1130	61	
1 3/4"	44.5	55	10	150	30	450	0.9	270	1295	61	
2"	50.8	62	10	150	30	450	0.9	300	1567	61	
2 1/2"	63.5	74	10	150	30	450	0.9	380	1976	61	
3"	76.2	88	10	150	30	450	0.9	460	2545	61	
3 1/2"	90	103	10	150	30	450	0.9	540	3256	61	
4"	101.6	116	10	150	30	450	0.9	600	4020	61	
5"	127	143	10	150	30	450	0.9	760	5730	61	
6"	152.4	170	10	150	30	450	0.9	900	7850	61	
8"	203	224	10	150	30	450	0.8	1150	12170	61	
10"	254	278	10	150	30	450	0.8	1650	18560	61	
12"	305	331	10	150	30	450	0.8	1900	24630	61	