



## FLX-SAND 12

SANDBLAST HOSE 12 Bar W.P.

### Application

Used in conveying sand, shot, glass beads and other abrasive materials at high velocity for cleaning metal, concrete surfaces at shipyards and general construction.

### Tube

Black, smooth, static-dissipating NR/SBR rubber compound.

### Reinforcement

High strength multiple synthetic plies, anti-static copper wire.

### Cover

Wrapped impression, abrasion and weather resistant, pin-pricked, static-dissipating, NR/SBR rubber compound.

### Temp. Range

-40°C to +70°C ; -40°F to 158°F



ID



OD



WP



BP



BR



W



L

inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/2"	12.7	25	12	175	36	525	127	460	61
1/2"	12.7	27	12	175	36	525	127	544	61
5/8"	16	30	12	175	36	525	160	637	61
3/4"	19	30	12	175	36	525	195	550	61
3/4"	19	33	12	175	36	525	195	708	61
1"	25.4	40	12	175	36	525	250	934	61
1 1/4"	32	48	12	175	36	525	320	1224	61
1 1/2"	38	54	12	175	36	525	380	1415	61
1 1/2"	38	56	12	175	36	525	380	1585	61
1 3/4"	44.5	60	12	175	36	525	450	1520	61
1 3/4"	44.5	63	12	175	36	525	450	1850	61
2"	50.8	69	12	175	36	525	500	2080	61
2"	50.8	73	12	175	36	525	550	2697	61
2 1/2"	63.5	82	12	175	36	525	630	2602	61
3"	76.2	96	12	175	36	525	760	3236	61
4"	101.6	122	12	175	36	525	1010	4304	61

Abrasion loss value: Acc ISO 4649:2021 < 35 mm3